



Eye & Eye Round Slings



Soft, Supple & light weight, easy to use.
 Super flexible, conforms to shape of load, flattened and lift the load securely.
 Works well for confined spaces.
 All advantages of Flat Web slings & Round slings.
 Extra Sleeves cab be added to body easily.
 Adapts to all sizes, types and load configurations.
 Light weight and pliable for easy lifting and storage.
 Colour coded for easy identification.
 Available in safety factor 7:1 and 5:1
 Free overload tail indicator yarn and optical fiber



			EYE TO EYE ROUND SLINGS CAPACITY IN KGS								
			WLL in kg with one Round Sling				WLL in kg with two Round Slings				
			Straight lift	Choke Hitch	Basket Hitch			Straight Inclination		Choke Inclination	
ITEM CODE	DIA	COLOUR CODE			up to 7°	7° - 45°	45° - 60°	7°-45°	45°- 60°	7°-45°	45°- 60°
MODE FACTOR			M=1.0	M=0.8	M=2	M=1.4	M=1.0	M=1.4	M=1.0	M=1.12	M=0.8
LREE-1	18	VIOLET	1000	800	2000	1400	1000	1400	1000	1120	800
LREE-2	20	GREEN	2000	1600	4000	2800	2000	2800	2000	2240	1600
LREE-3	22	YELLOW	3000	2400	6000	4200	3000	4200	3000	3360	2400
LREE-4	25	GREY	4000	3200	8000	5600	4000	5600	4000	4480	3200
LREE-5	28	RED	5000	4000	10000	7000	5000	7000	5000	5600	4000
LREE-6	32	BROWN	6000	4800	12000	8400	6000	8400	6000	6720	4800
LREE-8	38	BLUE	8000	6400	16000	11200	8000	11200	8000	8960	6400
LREE-10	46	ORANGE	10000	8000	20000	14000	10000	14000	10000	11200	8000
LREE-12	58	ORANGE	12000	9600	24000	16800	12000	16800	12000	13440	9600
LREE-15	70	ORANGE	15000	12000	30000	21000	15000	21000	15000	16800	12000
LREE-20	78	ORANGE	20000	16000	40000	28000	20000	28000	20000	22400	16000
LREE-25	90	ORANGE	25000	20000	50000	35000	25000	35000	25000	28000	20000
LREE-30	100	ORANGE	30000	24000	60000	42000	30000	42000	30000	33600	24000
LREE-36	115	ORANGE	36000	28800	72000	50400	36000	50400	36000	40320	28800
LREE-40	150	ORANGE	40000	32000	80000	56000	40000	56000	40000	44800	32000
LREE-50	180	ORANGE	50000	40000	100000	70000	50000	70000	50000	56000	40000



Use Anti-Abrasive, Anti-cut Sleeves to protect round slings from damage by sharp edges, we have wide range of protection sleeves (see Sling Protection)



Aperture angles of eyes should not be more than 20°. It means length of the eye equals or exceeds four times the area of support of the lifting hook.