

MS EYE BOLT



S.W.L at 0 kg	Size Dia A	Coarse Pitch	B	D	E	F	G	H	M	Approx Weight each kg
85	8	1.25	20	6	20	8	18	12	10	0.06
150	10	1.50	25	8	25	10	22	18	12	0.11
220	12	1.75	30	10	30	12	26	22	14	0.18
380	16	2.00	35	12	35	14	30	28	16	0.28
570	20	2.50	40	14	40	16	35	30	19	0.44
810	22	2.50	45	16	45	18	40	35	21	0.55
1,050	24	3.00	50	18	50	20	45	38	24	0.74
1,700	30	3.50	65	22	60	24	55	45	28	1.66
2,500	36	4.00	75	26	70	28	65	55	32	2.7
3,400	42	4.50	85	30	80	32	75	65	38	4.0
5,200	48	5.00	100	35	90	38	85	70	46	6.4
6,500	56	5.50	110	38	100	42	95	80	50	8.8
8,700	64		120	42	110	48	105	90	58	
13,000	72		150	50	140	60	130	105	72	
17,000	80		170	55	160	68	150	120	80	
20,000	100		190	60	180	75	165	130	88	

HIGH TENSILE EYE BOLT



Thread Size D	S.W.L.@ 0 (kg.)	A mm	B mm	E mm	F mm	G mm	H mm	J mm	Coarse Pitch
M 8	160	6	20	20	6.3	20	15	1	1.25
M 10	250	7.7	24	24	8	25	17	1	1.5
M 12	400	9.4	28	28	9.5	30	20	1	1.75
M 16	630	13	34	34	12.5	36	24	1	2.0
M 20	1000	16.4	40	40	16	45	27	1	2.5
M 24	1600	19.6	48	48	19	53	31	2	3.0
M 30	2500	25	56	56	24	64	39	2	3.5
M 36	4000	30.3	67	67	28	75	48	3	4.0
M 42	6300	35.6	80	80	34	90	56	3	4.5
M 48	8000	41	95	95	38	100	65	3	5.0
M 56	10000	48.3	112	112	45	119	73	4	5.5
M 64	16000	55.7	125	125	50	135	85	4	6
M 72	20000	63.7	140	140	58	153	95	4	6.0
M 80	25000	71.7	160	160	63	165	110	4	6.0
M 90	30000	81.7	180	180	71	180	125	5	6.0
M 100	40000	91.7	200	200	80	195	140	5	6.0



