

CARESEAL GS204

Grout Sealer

CARESEAL GS 204 Grout Sealer is an affordable, water-based penetrating sealer that will provide protection against most common stains for sanded and non-sanded cementitious grout joints. It can also be used as a pre-grouting sealer. CARESEAL GS 204 is an aqueous fluorochemical dispersion that provides a durable, subsurface, transparent protective barrier against oil and water on porous mineral surfaces such as stone and tile. The product is used in waterbased penetrating sealers for stone, unglazed tile, grout, terra cotta, and other porous mineral surfaces such as concrete and brick. CARESEAL GS 204 provides oil and water repellency, stain resistance, and easy stain cleanup.

FEATURES

- Water based sealer
- Protection against most common stains
- Easy to apply and will not alter the colour of the grout joint
- For interior and exterior applications
- VOC comply

USES

Recommended for indoor and outdoor use, on a wide variety of surfaces, including natural stone, tile, paving, brick, kitchens, bathrooms, laundries, pool surrounds, garages, entertainment areas and patios. Can be used on porous tile, natural stone, masonry.

TYPICAL PROPERTIES

Appearance	Clear
Stability	Stable at extreme temp. variations
Flash Point	Non- Flammable
Physical state	Liquid

SURFACE PREPARATION

Surface must be dry and free of contaminants , including previously applied sealers , dirt ,lime and hard water deposits , rust and other heavy soil and grime.

- Allow new grout installations to cure for at least 48 hours before application
- Surface and sealer temperature should be between 5C° and 46C°

PACKING

5 L , 20 L

STORAGE: Store materials between 40°-90°F with careful handling to prevent damage to products. If conditions exceed these ranges, special consideration in storage must be taken. Do not store at high temperatures in direct sunlight. Shelf life under normal conditions in closed container will be 12 months.

WARRANTY

On preapproved, qualified applications, when you use an approved applicator, a 25-year warranty is available. Contact us for complete warranty information.



engineered to perform

