



TM

Reverse Osmosis Tank

pure water always!



Cold Rolled Carbon Steel



304 Stainless Steel Connector



Triple Coated Liquid Paint



Heavy-Duty Butyl Rubber



FDA Grade Polypropylene
Brass cap with internal O-ring



7 PSI / 0.5 Bar



93°C / 200°F



150 PSI / 10 Bar

SPECIFICATION

Model Number	Total Tank Volume		Diameter		Height (Base Including)		N.W.		G.W.		Shipping Volume
	Liter	Gal	cm	Inch	cm	Inch	kg	Lbs.	kg	Lbs.	CUF
WRO 3	3	0.5	13.0	6.0	21.5	8.6	13.8	30.4	14.5	31.9	2.00
WRO 8	8	2	17.6	8.0	28.5	11.4	2.3	5.1	2.5	5.5	0.52
WRO 12	12	3.2	23.6	9.3	39.5	15.8	3	6.6	3.2	7.1	0.73
WRO 24	24	6.0	28.0	11.0	41.5	16.6	4.2	9.2	4.6	10.1	1.32
WRO 60	58	14	38.1	15.0	64.0	25.6	9	19.8	9.7	21.4	3.80
WRO 80	80	20	38.1	15.0	79.0	31.6	12.2	26.8	13	28.6	4.70
WRO 100	100	28	38.1	15.0	101.0	40.4	15	33.0	15.5	34.1	6.00
WRO 130	130	34	55.9	22.0	75.8	30.3	20.8	45.8	22	48.4	8.40
WRO 160	160	44	55.9	22.0	93.0	37.2	24.1	53.0	25.5	56.1	10.30

Note :

- > WRO 3 & WRO 8 is In-line model.
- > WRO 12, 24, 60, 80 & 100 vertical with plastic stand.
- > WRO 130 & WRO 160 is vertical with welded stand.
- > Volume above is total capacity of the tank.

Dealer/ Distributor



Reverse Osmosis Tank

pure water always!

Reverse Osmosis Tanks are constructed using the finest FDA approved material.

Lead safe technology applied on the stainless steel connector for the pre-pressurized water storage tank are the standard for industry for drinking water application. Structural integrity, deep drawn domes and precision weld gives our reverse osmosis tank unparalleled reliability. The poly propylene liner, and Butyl diaphragm are made with FDA approved materials and prevent water from making contact with metal tank for cleaner, fresher, odourless water. It promise to deliver user pure pristine water when filling of your glass. The Butyl rubber is made with a unique ingredients and compound which has a best air resistance comparing with other tank in the market. Sealed brass air valve with internal O-ring ensure leak free air chamber, hence no maintenance is needed during service life.

FEATURES :

- Patented stainless steel water connection.
- High grade Butyl diaphragm.
- Virgin polypropylene liner.
- Smooth internal construction prevents diaphragm abrasion damage.
- Triple coated liquid paint.
- NSF approved.
- Comprehensive testing.
- Maintenance Free.



A QUALITY PRODUCT BY :

WATERINO

email: admin@waterino.com

www.waterino.co.in
www.waterino.com

