



N-G4W
Made to Dominate







Finger



RFID



Battery (Optional)



WiFi



LAN



USB



GPRS



Access

# Multi-Bio Attendance and Access Control System

## Storage Capacity

Face Capacity	10,000
Finger Capacity	30,000
Card Capacity	10,000
Max User	10,000
Log Capacity	2,00,000

#### **Fetures**

World-class Face Identification Technology

High-Speed and Accurate Fingerprint Identification

Face, Fingerprint, Card authentication

2 output relay for door open.

Self-Service Inquiry

Good adaptation for dry, moist and rough fingerprints.

Not necessary of bright lights during scans.

supremely low Electric energy consumption.

Comprehensive SDK is available for development & integration.



# Communication Interface

Communication WIFI, TCP/IP, RS232/485, USB

#### **Biometric**

Push Data	Yes
4G GPRS	Yes (Optional)
Printer	Yes (Optional)
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
Processor	1 GHz
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



Auto Focus



low light Verification



Long Distance Verification



Accepts Color Finger

### Audio/Visual

LCD	4.3" touch screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software Desktop, Web, Cloud

#### Access control

Wiegand in & out	YES
Relay	YES
Support	RS485 Reader, Wiegand Reader,
	Remote, Push Button, No Touch



Time Attendance



Access Control



Employee Self Service



Mobile App

Connect with us on

### Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	192 x 146 x 95 mm

**Disclaimer**: Brief specifications are mentioned here, specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.



BiomaxOfficial





