



Retail Solutions

# THERMAL PRINTER

Receipt + Label Printer



# PARAMETER

## Basic Configuration

<b>Printing Method</b>	Thermal Line
<b>Printing Speed</b>	150mm/s
<b>Resolution</b>	8 dots/mm, 864 dots / line
<b>Printing Width</b>	108mm
<b>Character set</b>	ANK, Gb18030 (Chinese)
<b>Print Font</b>	ANK: 12 x 24,9x17, Chinese 24 x24
<b>Character per line</b>	48-Font A/64-Font B
<b>User Defined</b>	Support
<b>Language (Code Page)</b>	Support Simplified & Traditional Chinese English and Other 45 Kinds of international Character
<b>Paper Type</b>	Thermal Paper
<b>Paper Width</b>	25.4-108m
<b>Paper Roll Diameter</b>	Max: 100.0mm
<b>Paper Thickness</b>	0.056 to 0.1mm
<b>Paper Supply Method</b>	Drop-in paper load
<b>Auto cutter</b>	Null
<b>TPH</b>	100km
<b>Barcodes</b>	UPC-A,UPC-E,EAN-13,EAN-8,CODE39,ITF, CODEBARCODE93, CODE128,QR CODE, PDF417
<b>Commands set</b>	ESC/POS
<b>Driver</b>	windows(WIN / Wn8 / WIN10/VISTA/XP/2000)
<b>Sensor</b>	Paper Out
<b>Drawer port</b>	1 Port, RJ11-6P6C SOCKET 24v
<b>Interface</b>	USB Drawer port
<b>Power Supply Adapter</b>	AC100~240V(+/-10%) DC24V,2.0A
<b>Life</b>	Null
<b>Net weight</b>	1.5kg
<b>Gross Weight</b>	2.0kg
<b>Printer Dimension (LxWxH)</b>	200x175x143 mm