

Introduction Of Dry Laser Particle Size Analyzer

Model No.: Winner-3003



Overview:

Winner3003 is a universal dry dispersion laser particle size analyzer, using the scientific structure design and a new generation of dispersion device, the dispersion effect is better than similar instruments. Using MIE scattering theory as the theoretical basis, converging Fourier transform optical path, and with high stability and He-Ne laser high-sensitivity photodetectors ring ensures repeatability and accuracy of test results.

This product use air as the dispersing medium, the use of turbulent dispersion principle, with high-precision feeding apparatus and Patent powder injection pumps, No-Oil silent air source, ensure that the sample is thoroughly dispersed. It is applied to any powder material, particularly good for materials occurs chemical reaction in water, or shape change in the liquid. It have same accuracy and repeatability compared with the wet method.



Main Specifications:

Model Name		Winner3003
Size Range		0.1μm-300μm
Standard		ISO13320-2020, GB/T19077.1-2008, Q/0100JWN001-2013
Channels Number		40 pcs
Accuracy error		<1% (Deviation of D50 on national standard sample)
Repeatability error		<1% (Deviation of D50 on national standard sample)
Light Source		Red Fiber Laser (λ = 632.8nm, P>2.0MW)
Dispersion Method		Dry-turbulence dispersion mode
Operation Mode		Manual/Automatic
Optical Path Calibration System		Three dimension alignment
Dispersing Medium		Compressed air
Test Speed		<1min for each time
Connection Port		USB
	Analysis mode	Free Distribution, R-R Distribution, Logarithm Normal
		Distribution, Mesh number classification
	Statistic Method	Volume Distribution, Quantity Distribution
	Statistic	Several Testing Results of samples
	Comparison	Different batches of samples testing result,
		Samples before and after processing,
Software		Test result of samples in different time.
function		
	User-defined	Figure out percentage according to the particle size
	Analysis	Figure out particle size according to the percentage
		Figure out percentage according to the particle size range
		Meet demands of representation of particle test in different
		industries.
	Test Report	Word, Excel, Photo(Bmp), Text etc
	Multi-language	Chinese&English
	Support	
	Intelligent	Automatically control Air flow speed, dispersion, test and
D	Operation Mode	analysis.Better Repeatability after remove human-factor
Request computer configuration		Windows XP/Windows 7/ Win 10- 64 bits, Core i3/better 2G, Hard
X7.1		disk 160G, Disk D
Volume		L88cm×W40cm×H30cm
Net Weight		36Kg



Main Features:

1) Unique patent technology of optical path and detection system, greatly improve testing resolution.

Converging Fourier transform optical path patent technology overcome lens aperture restriction on the scattering angle, expand testing range in limited space, and add more secondary integrated photodetectors, which can effectively collect scattered light from all angles in the the corresponding test range, make sure the testing accuracy and reliability within the full range.

2) Scientific and automatic dry dispersing system

Turbulence dispersion patented technology and Normal shock shearing effect make particles sufficient dispersion, dispersion core part using wearable ceramics not only improve dispersion system's working life but ensure more accurate and stable testing result.

3)Intelligent Operation System realize one key test

Just need put in sample, Dust collection, air supply, feeding and others are all automatic. It only only reduces workload, but eliminate errors caused by human factors, further improve testing accuracy and authenticity of the testing results.

4)Software support

Unique unconstrained free fitting technology make particle analysis not be restricted by any functions, truly reflect particles distribution, ensure accuracy of testing result.

Application:

Winner3003 Dry laser particle size analyzer used in cement, ceramics, pharmaceuticals, dyes, pigments, fillers, chemical products, catalysts, coal dust, additives, pesticides, explosives, graphite, photographic materials, fuel, metal and non-metal powder, carbonated calcium, kaolin and other powder industry, particularly for materials which occurs chemical reaction, the shape change and the loss in the liquid, such as herbs, magnetic materials and relatively wide distribution and larger particles powders, have more unique applicability and practicality.



Patents Technology:

- Optical bench design is protected by patent No.- ZL 2014 2 0378380.8,
- Three dimensional-optical bench alignment system is protected by patent No.- ZL 2013 2 0835882.4.
- MIE scattering principle application patent No.- ZL 2013 2 0812021.4.
- Dry particle size analyzer full sealed sample cuvette application is protected by patent No.-ZL.2011 2 0267646.8.
- Powder dispersion pump design application is protected by patent No.-ZL 2007 2 0018648.7

Principle:

