
❑❑Product Brochure: Portland Slag Cement (PSC)

❑ 📖Product Overview

Portland Slag Cement (PSC) is a blended cement made by mixing Ordinary Portland Cement (OPC) with granulated blast furnace slag. It offers superior resistance to chemical attacks, reduced heat of hydration, and long-term durability—making it ideal for marine, industrial, and mass concrete applications.

❑ 📋Technical Specifications

Attribute	Details
Type	Portland Slag Cement (PSC)
Packaging Size	50 kg per bag
Packaging Type	HDPE Sack / PP Sack
Compressive Strength	≥ 43 MPa (28 days)
Initial Setting Time	≥ 30 minutes
Final Setting Time	≤ 600 minutes
Color	Grey
Shelf Life	3 months from date of manufacture
HS Code	2523.2940

❑ 📦Export Details

- **Place of Origin:** India
 - **Port of Loading:** Tuticorin / Chennai / Mundra
 - **Incoterms Available:** FOB / CIF / EXW
 - **Container Capacity:** ~480 bags per 20-ft container (24 MT max)
 - **Delivery Time:** 30–45 days
 - **Minimum Order Quantity:** 1 container (480 bags)
-

❑ 🏗️Applications

- Marine structures
 - Sewage and water treatment plants
 - Mass concrete works
 - Industrial foundations
 - Coastal infrastructure
-

□□Price Range (Indicative)

INR
8000/ton

Prices vary based on quantity, packaging, and destination. CIF quotes available on request.

✓ Certifications & Trust

- GST & IEC Verified Exporters
 - TrustSEAL Certified Suppliers
 - Verified on IndiaMART & Global Trade Plaza
 - ISO 9001:2015 Compliant Manufacturers
-

□ 📞Contact & Orders

To place an order or request a quote, please provide:

- Quantity required
 - Destination port
 - Preferred Incoterm (FOB/CIF/EXW)
 - Packaging preference (HDPE/PP Sack)
-