

CETPLAST CA

1417

Concrete admixture

Description:

CETPLAST CA is a general purpose concrete admixture. It helps in achieving increased workability in all grades of concrete and better retention of slump using economical dosage

Advantages:

- Increased workability
- > Easier placing compaction and finishing
- ➤ Higher cohesion- reduces risk of segregation & bleeding.
- Increased strength and durability
- Lower water requirement for given workability.

Area of application:

- > In pre-stressed concrete.
- In pre-cast concrete manufacture.
- Congested reinforcement where high work workability is required.

Properties:

> Appearance : Brown liquid

Specific Gravity : 1.18

IS Standard
9103 - 1979
ASTM Standard
C-494-86 Type A

Direction for use:

Add the required dosage to the gauging water

Dosage: 150 g to 250 g per 50 kg cement

Packing: Supplied in 20, 50 kg, & 225 kg

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products

CETCON Building Technologies Pvt. Ltd.

13, Milan Estate, Opp. Shah Foils Ltd, Santej- Khatraj Road, At: Santej,

Dist: Gandhinagar - 382721, Gujarat, India.

Mobile: +91-97279 00055, +91-97129 00055, Fax: +91-79-2759 1055

Email: contact@cetconindia.com, Website http://cetconindia.com

Reg. Office: C-301, Akash Residency, GST Crossing, New Ranip, Ahmedabad – 382470

CIN: U24132GJ2013PTCO73641



An ISO 9001:2008 Certified Company