



## CETFIX BLA

2017

Polymer modified Block Laying adhesive.

### Description:

Cetfix BLA is polymer modified cement based powder needs to be mixed with water for installation AAC block. The unique chemical combination enables this mortar to be more compact, thinner and more versatile at only 3 mm thick against 12 to 18 mm conventional mortar.

### Advantages:

- High adhesive strength, Improve overall masonry strength and load bearing capacity.
- Excellent bonding and waterproofing.
- Pre-mixed and ready to use, only water is to be added at site.
- No water curing is required after application, so plastering just after 24 hours of application.
- Easy to mix and easy to use. Reduces labour cost.

- Economical – quantity of mortar is far less than conventional mortar

### Area of application:

- Laying and jointing of masonry, AAC blocks, fly ash bricks, and hollow blocks.
- Jointing of pre-stressed concrete slabs, panels.
- Jointing of concrete window and door frames.

### Direction of use:

### Mixing:

- Mix 3 parts cetfix BLA and 1 part of water by volume to stiff consistency. Leave for 5 minute, remix and use within 45 minutes.

### Application:

- Apply a thin uniform layer of cetfix BLA 3 to 4 mm thick, on the levelled surface of masonry units using proper trowel.
- Place the next course of masonry units on the evenly laid jointing mortar bed in proper line & level.
- Clean the excess material, if any immediately, Continue the procedure for the entire masonry works.

### Coverage:

6 to 6.5 sqm. per 20 kg bag at 3 mm bedding thickness.

### Packing:

Supplied in 20 kg bag.

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products



## CETCON Building Technologies Pvt. Ltd.

13, Milan Estate, Opp. Shah Foils Ltd, Santej- Khatraj Road, At: Santej,  
Dist: Gandhinagar - 382721, Gujarat, India.

Mobile : +91-97279 00055, +91-97129 00055, Fax : +91-79-2759 1055

Email : [contact@cetconindia.com](mailto:contact@cetconindia.com), Website <http://cetconindia.com>

Reg. Office: C-301, Akash Residency, GST Crossing, New Ranip,  
Ahmedabad – 382470.

CIN : U24132GJ2013PTCO73641

