

Capacity		Rx350	Rx500
Swing Over Bed	mm	500	500
Maximum Turning Diameter	mm	300	350
Standard Turning Diameter	mm	200	230
Max.Turning Length (with chuck)	mm	300	500
Admit Between Centers	mm	350	550
Chuck Size	mm	200	210
TRAVERSES			
Cross (X-Axis) Travel	mm	175	175
Longitudinal (Z-Axis) Travel	mm	350	550
Rapid Feed (X & Z Axis)	m/min	15/25	15/25
MAIN SPINDLE			
Spindle Motor Power	Cont/30 min	7.5/11 kw	7.5/11 kw
Spindle Bore	mm	38	56
Spindle Nose		A2-5	A2-6
Max.Bar Capacity	mm	40	48
Spindle Speed Range	rpm	50-4000	50-3500
Full Power Speed Range	rpm	1000-3300	1000-3000
TAIL STOCK			
Quill Dia.	mm	80	80
Quill Taper	mm	MT4	MT4
Quill Stroke	mm	100	100
Base Travel	mm	250	400
TURRET			
No.of Tool Position	No.	8	8
Tool Shank Size	mm	25x25	25x25
Max.Boring Bar Dia.	mm	40	40
CNC System	Make	GSK988T/Fanuc Oimate/Siemens	
Accuracy (As Per VDI/DGQ 3441)			
Positioning Uncertainty	mm	0.007	
OTHER			
Weight (Approx.)	Kgs	3500	3900
Dimension (Approx.)	(LxWxH)	2300x1450x1800	2600x1450x1800

