




KINGDOM GROUPS FZE



ISO9001:2008
Registered company by IIC (No: JU- 1306)

SAE 10W40 API CJ-4 KINGDOM GOLD TURBO DIESEL ENGINE OIL WITH 10000 KM PLUS Warranty (FULLY SYNTHETIC OIL)

Performance Standard: API CJ-4

Manufacturer: Kingdom Lubricants Factory LLC, UAE

SAE 10w40 API CJ-4 KINGDOM GOLD TURBO DIESEL ENGINE OIL is extra high performance diesel engine oil that provides excellent lubrication of today's diesel engine promoting extended engine life. This product meets or exceeds the specification of all major European and American engine manufacturers. This oil is recommended for use in turbo-charged diesel powered equipment from leading Japanese, European and American Manufacturers, mixed fleets, On-highway light and heavy-duty trucking, off highway industries including construction, mining, quarrying and Agriculture.

EVO

E- Extra Protection to Engine, Clutch & Gears

V- Value for Money with 70% Extra Mileage

O- Outstanding Performance in all Weathers

SPECS

-Meets or exceeds the requirements of KINGDOM EVO diesel engine oil

Features	Advantages
Broad Viscosity Range	Superior protection and performance in all weather conditions throughout year
Good Anti Wear Properties	Extends Engine Life
High Thermal Stability & Oxidation Stability	Keeps Engine Clean for smoother operation
Good Corrosion Protection	Maintains excellent control of oil consumption.
Advanced detergency leading to cleaner engines and longer component life.	Excellent Wet clutch performance



KINGDOM GROUPS FZE



ISO9001:2008
Registered company by IIC (No: JU- 1306)

Performance Levels:

- API CJ-4
- ILSAC GF-5
- ACEA E9,E7
- VW VDS-4
- BMW Special Oil
- MB 235.28,228.51,228.31
- Caterpillar ECF-3
- MTU Oil Category 3.1
- Mack EO-O Premium plus

Always follow equipment manufacturer's recommendation for the required lubricant performance level and oil drain interval.

Typical Properties:

SAE Grade	10w40
Appearance	B&C
Viscosity @40 °C ASTM D 445, CST	101.35
Viscosity @100 °C ASTM D 445, CST	14.98
Viscosity Index ASTM D 2270	155
Flash Point, COC ASTM D 92	225
Pour Point, °C ASTM D97	-33
Density @ 15 °C ASTM D 4052	0.87
TBN (mg KOH/gm) ASTM D 2896	10.5
Sulphated Ash, WT % , ASTM D874	<1.0
CCS , CP, ASTM D5293	6600@ -25 °C
Volatility, % off @ 250 °C ASTM D5800	10-12 max

Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.