




## KINGDOM GROUPS FZE



ISO9001:2008  
Registered company by IIC (No: JU- 1306)

## BASE OIL SN-650

### Description

SN 650 is defined as a light grade base oil at the upper end of the specifications for Grade I base oils. They are mainly used in lubricant production. It is a Group I base oil which has undergone solvent refining and dewaxing processes. To finish the refining it was hydrogen treated to clear out any impurities.

### Application

SN 650 serves as a base stock for several industrial lubricants

- General purpose oils
- Mould oil
- Transmission fluids
- Gear oils
- Metal working fluids
- Additives

And also

- Hydraulic oils
- Transformer oils

### Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.



## KINGDOM GROUPS FZE



ISO9001:2008  
Registered company by IIC (No: JU- 1306)

### Quality Specification\*

Parameter	Unit	min/max	Value
ASTM Colour	-	max	2.5
Density at 15°C	(kg/m3)	max	897
Kinematic Viscosity at 100°C	(cSt)	-	13.5-14.5
Kinematic Viscosity at 40°C	(cSt)	-	130-150
Viscosity Index	(typical value)	-	92-95
Pour Point	(°C)	max	-9
Flash Point	(°C)	min	245
Sulphur Content	(%m/m)	max	0.8

*\*Disclaimer: Data mentioned in this document and on our site is meant to enable readers to orient themselves about the properties and possible applications of our products and is subject to change without notification.*