



## KINGDOM GROUPS FZE



ISO9001:2008  
Registered company by IIC (No: JU- 1306)

### AUTO COOL 40%

**Performance Standard: BS 6580**

**Manufacturer: Kingdom Lubricants Factory LLC, UAE**

Auto cool is recommended for use in liquid cooling systems of automotive and industrial gasoline and diesel engines.

#### Applications

Auto cool protect cooling systems of gasoline and diesel against rust in all seasons. It provide ideal cooling, effective protection against corrosion and scale deposit.

Features	Advantages
Good dispersing characteristics	Provides rust and corrosion protection
Provides rust and corrosion protection	Resistant to water-washing and wet conditions
Wide range of usable temperature	Outstanding thermal and oxidation stability over extended periods

#### Typical Properties:

Grade	<b>40%</b>
Appearance, Color	<b>Blue</b>
Density @ 20 °C , ASTM D-1298	<b>1.050</b>
PH, ASTM D-1287	<b>7.9</b>

#### Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.