








Construction	Diameter (mm)	Min. Breaking Load(Kg)		
		Galvanized	SUS 316	SUS 304
 1X7	0.30	10	8	10
	0.40	18	15	17
	0.50	29	25	27
	0.60	41	34	39
	0.80	72	60	68
	1.00	110	90	105
	1.20	155	135	150
	1.40	210	180	205
	1.50	240	210	230
	1.60	270	240	260
 1x12	1.00	105	80	95
	1.20	150	120	140
	1.40	200	160	190
	1.50	230	185	215
	1.60	250	210	245
	1.80	310	265	310
 7x7	1.20	120	115	120
	1.50	180	170	175
	1.60	220	205	210
	1.80	260	250	260
	2.00	310	290	300
	2.50	480	465	470
	3.00	700	675	690
	3.50	920	900	910
	4.00	1,200	1,050	1,100
 1x19	0.80	70	50	60
	1.00	105	80	95
	1.20	150	120	140
	1.40	220	160	190
	1.50	250	185	215
	1.60	280	210	245
	1.80	340	265	310
	2.00	425	330	365
	2.50	665	520	570
	3.00	850	660	730
	3.50	1100	860	950
 1x37	2.50	580	440	555
	3.00	830	640	800
	3.50	1130	870	1090
	4.00	1480	1140	1420
	4.80	2130	1640	2050
	5.00	2300	1670	2110
	6.00	3330	2400	3000
Construction		Material	Diameter (mm)	Min.torque Load(Kgf)
		Galvanized Black	3.15	12.5

SPEEDO INNER (1+4+4+6+6)	Galvanized Black + Brass	3.15	12.5
-------------------------------------	-----------------------------	------	------


Approx Weight (Kg/100m)
0.05
0.08
0.13
0.18
0.32
0.50
0.74
1.01
1.15
142
1.63
2.05
0.49
0.70
0.95
1.09
1.24
1.58
0.61
0.95
1.08
1.34
1.65
2.57
3.71
5.05
6.60
0.32
0.50
0.72
0.98
1.12
1.27
1.61
2.00
3.10
4.48
6.00
7.90
12.50
18.10
3.05
4.39
5.99
7.82
11.3
12.20
17.60
Approx Weight (Kg/100m)
0.0467

0.0467

OUTER CASING FOR CONTROL CABLES

Construction		Diameter (mm)	Types
	OUTER CASING (SINGLE PLY)	5.0	With & without coating
		6.0	
		7.0	
		8.0	

OUTER CASING FOR SPEEDO METER CABLES

Construction	Diameter (mm)
	OUTER CASING (DOUBLE PLY)
	7.0