



KAMSONS CHEMICALS PVT. LTD.

Plot No. A-726, T.T.C. Industrial Area, Village Mahape,
Thane Belapur Road, Dist. Thane, Navi Mumbai. INDIA.

Ph: (91)22-27780768, (91)22-27780765, (91)22-42029999, Fax: (91)22-42029975

CIN NO: U24100MH1996PTC099064

PRODUCT INFORMATION DATA SHEET

Concrete Sealer Topcoat Kamicryl-CS0003

Description/Use

Kamicryl-CS0003 is a newly developed ultra premium water base concrete sealer utilizing the latest available technology. The coating incorporates 100% water base polyurethane technology offering superior overall properties and performance.

Areas of Use

Designed to be used for topcoat application over epoxy coatings on concrete substrates, or when used in conjunction with Kamicryl- CS0002 Primer, the system is highly durable and suitable for medium trafficable driveways, pathways, car parks, and garage floors.

Special Features

- *Excellent wet look and minimal colour change to substrate
- *Excellent early water resistance
- *Excellent chemical and solvent resistances
- *Low VOC at less than 22g per Liter
- *Excellent exterior durability and low yellowing
- *Excellent dirt and stain resistance

Thinning

Not required – ready for use

Method of Application

Brush, roller or spray.

Satisfactory with most equipment. Observe the State Spray Painting Regulations.

Do not apply if temperature is below 10°C or likely to fall below 10°C

Do not apply if rain is expected or in extreme hot dry conditions.

Drying(25° C & 50%R.H.)

Dry to touch- 30 Minutes

Recoatable-3 Hours

Coverage

Approximately 16 sqm/Lt/Coat
Recommend 2-3 coats for optimum performance and durability Coverage will vary depending on the profile and porosity of the surface.

SurfacePreparation

Green Concrete Allow concrete to fully cure as required. Remove all loose material and wash with clean water and allow to dry.

Due to the numerous coating additives used in concrete mixture by numerous suppliers, it is necessary to perform numerous adhesion spot test checks of reasonable size. Apply the coating and allow a minimum 48 hours to dry and perform an adhesion test according to AS/NZ1580.408.2 - Knife Test and AS/NZ1580.408.4 - Cross – Cut.

Health&Safety

- * Keep out of reach of children
- * Wear protective clothing
- * Ensure good ventilation if using inside
- * Do not breathe vapour or spray
- * Do not smoke
- * Wear eye protection
- * Store in a cool place

FirstAid

Eye Contact – rinse with cold running water for 10 to 15 minutes. Seek medical attention if irritation persists.
If Swallowed- drink large amounts of water and seek medical attention.

Environment

Do not tip unused paint or washings down drains
Dispose of waste using authorized collection procedures.

Disposal

When cleaning up after painting, ensure that paint does not get into Gutters or drains as it may contaminate waterways.
Do not reuse empty can, this can is recyclable. Check with your local Council to see if it is participating in a steel can recycle programme.

Disclaimer: THESE SUGGESTIONS & DATA ARE BASED ON INFORMATION, WE BELIEVE TO BE RELIABLE. THEY ARE OFFERED IN GOOD FAITH, BUT WITHOUT GUARANTEE, AS CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL.
