

Transistor Tester

TT-825

HTC
INSTRUMENTS



Features :

- 3½ Digit LCD Display
- 2000 Counts
- Data Hold Function
- Auto Range
- Measuring forward voltage, reverse voltage, forward saturation voltage drop, amplification factor, reverse leakage current of various crystal diode, audios, silicon controlled rectifier(SCR), field effect transistor(FET)
- Measuring rated working voltage of chemical capacitor, ethylene capacitor, a capacitor, leaded multilayer ceramic capacitor, high voltage locker.
- Measuring protection voltage of varistor.
- Measuring starting voltage of neon bulb, neon lamp.
- Measuring constant voltage value of 78, 79 series three-pole circuit.

Technical Data :

| Basic Functions | Range | Basic Accuracy |
|----------------------|-------------|-----------------------------------|
| $V_{(BR)}$ | 1000V | Breakdown of Current <1mA |
| $V_{CC(\text{set})}$ | 200V | Breakdown of Current <1mA |
| | 2A(Ic) | Ic approx 2000mA, Ib approx 200mA |
| HFE | 800mA(Ic) | Ic approx 800mA, Ib approx 80mA |
| | 100mA(Ic) | Ic approx 100mA, Ib approx 100A |
| | 10mA(Ic) | Ic approx 10mA, Ib approx 1mA |
| | 10mA(Ib) | Ib approx 10mA |
| Iceo | 1mA(Ib) | Ib approx 1mA |
| | 1uA(Ib) | Ib approx 0.01mA |
| | 2000uA | Vcc approx 27V |
| Voltage of Three-end | 78xx / 79xx | Ui approx 27V |

- **Standard Accessories** : Hard case (Meter Enclosed), Test Leads, Manual
- **Dimension** : 150(H) x 100(W) x 70(D)mm