

BP-12C Technical Specifications

Product Specifications

1. Safety Specifications

1.1 Environment Specifications

Equipment Environment (Host, Recorder and IBP Module)				
Item	Temperature	Humidity (Non-Condensing)	Atmospheric Pressure	
Operating	5°C-40°C (41°F-104°F)	30%-80%	526mmHg-795 mmHg (70 kPa-106 kPa)	

1.2 Power Specifications

Power Supply	3*LR6 (AA) alkaline batteries or Ni-MH rechargeable batteries
Supply Voltage	4.5V
Operating Current	<50 mA
Continuous	> 30 hours
working time	

2. Physical Specifications

Weight	Net weight 210g (including batteries)	
Size (L×W×H)	145×74×29 mm (L×W×H)	

3. Data Storage

Data Record	Record data once every 1/2/4/8seconds, up to 70–hour
Duta Record	records.

4. Measuring Specifications

4.1 SpO2 Measurement

Transducer: dual-wavelength LED sensor with wavelength

Red light: 660 nm, Infrared light: 905 nm.

Maximal average optical output power: ≤ 2mW

SpO2 measuring range: 35~100%

SpO2 measuring accuracy:

 $A_{rms}\,{\leq}\,3\%$ for SpO2 range from 70% to 100%

Note: A_{rms} is defined as root-mean-square value of deviation according to ISO 9919.

SpO2 low over-limit setting range: 85%~99%

Default low over-limit: 85%

4.2 Pulse Rate Measurement

PR measuring range: 30bpm~240bpm

PR measuring accuracy: ± 2 bpm or $\pm 2\%$ (whichever is greater)

PR over-limit setting range: 25bpm~250bpm Default over-limit: High: 120bpm Low: 50bpm

4.3 Perfusion Index Display Range

0~20%



Shenzhen Biocare Bio-Medical Equipment Co., Ltd.

Headquarters #A735,7/F, Block A, Shenzhen Mingyou Industrial Products Exhibition & Procurement Center, Baoyuan Road, Xixiang Sub-district,
Bao'an District, 518102 Shenzhen, PEOPLE'S REPUBLIC OF CHINA

Factory: 2/F West, 4th Block, Dayang Road South, Fuyong Sub-district,
Bao'an District, 518103 Shenzhen, PEOPLE'S REPUBLIC OF CHINA

Tol: +86-755-2796088 Fax: +86-755-27960643

E-mail: sales@biocare.com.cn / support@biocare.com.cn