

# S.S. Platform Scale



## CTG-S Series



aczel



**Shock-Guard  
overload protection**



### Standard Features

- High resolution up to 15,000 counts.
- Easy to read (0.56") Bright LED / LCD Display.
- Net Gross function.
- Rugged construction suitable for industrial application
- Optional remote display available for customer.
- Environmentally protected load cells IP-67 class Stainless Steel Load cells for washdown application.
- Stainless Steel capsulated load cell for complete washdown application.
- SS Back Rail Support Provided.
- 304 or 316
- GMP, FDA Compliance.
- Auto-OFF Function for power saving.
- Safety overload 150% of the scale capacity.
- Dust Resistance membranes key.



**S.S. Indicator**



**Built-in Printing  
Indicator**



Optional



**A-Type S.S. Roller**

### Display

- 0.56" Bright RED LED / LCD display.

### Power Supply

- AC 230V + 10% 50-60Hz & with built-in rechargeable battery backup.

### Optional

- RS 232C Serial Interface Port Facility
- 4-20 mA, set point facility.
- A-Type S.S. Roller Ramp.
- Built-in Printing Indicator.

Model	CTG 50S	CTG 60HS	CTG 60S	CTG 100S	CTG 150S
Capacity	50 kg	60 kg	60 kg	100 kg	150 kg
Readability	5 gm	5 gm	10 gm	10 gm	10 gm
Pan Size (mm/inch)	400 x 400 / 15.6" x 15.6"		500 x 500 / 19.5" x 19.5"		
Display	Bright LED / LCD				
Power Supply	AC 230V + 10% 50-60Hz				

Model	CTG 200S	CTG 300S	CTG 500S	CTG 500S	CTG 1000S
Capacity	200 kg	300 kg	500 kg	500 kg	1000 kg
Readability	20 gm	20 / 50 gm	50 gm	50 gm	100 gm
Pan Size (mm/inch)	600 x 600 / 23.4" x 23.4"			750 x 750 / 29.25" x 29.25"	1000 x 1000 / 39" x 39"
Display	Bright LED / LCD				
Power Supply	AC 230V + 10% 50-60Hz				

Specification are subject to change without prior notice.  
Images shown are for illustrations purpose only.

**WORLD WIDE MARKETING**

**ACZET PVT. LTD.**

Unit E2, Plot No. 15, WICEL Estate, Opp Seepz Gate No. 1, Andheri (E), Mumbai 400 093. (INDIA)  
Tel. : +91-22-4243 7700 • Fax : +91-22-4243 7800 • E-mail : sales@aczel.com • Web : www.aczel.com