CO₂/O₂ Incubator AVS Series







Two Stage Regulator



Co, Analyzer



Internal HEPA Filter

Main Feature

- Setting on LCD, Display on LED
- Dual beam Infra-Red Sensor
- Round corner shelves system
- Airjacketed type
- Various applications
- Available Double stack up for saving space
- Safety Device for Gas monitor, Over Heat, Water Level
- Built in HEPA filter Unit (Option)
- Gas seal screen (Option)
- CE, KGMP, ISO 9001 Certificate

Optional Accessories

V2500F	RCOTwo :	stage Reg	ulat	or
V2500A	ACO CO ₂	Analyzer		
V2500AOO ₂ Analyzer				
V2500H Filter	HCO	Interr	nal	HEPA
VCO2UV-C Inner UVGL for Sterilization				
Monito	MT-PC oring sed data	Gas	S Y	Temp. ystem gger.

Laboratory CO2 Incubators deliver a higher level of performance for a dependable and reliable controlled in-vitro environment for optimum tissue cell culture growth. The chamber also provides an environment for the storage and preservation of gametes and animal tissue cell cultures at near body temperature. Advanced gas control systems create precise environmental conditions for your protocols requiring hypoxic conditions.

Model	AVS-2050CW/COW	AVS-2180CW/COW	
Capacity	50 Ltr.	180 Ltr.	
Shelves	2EA, Adjustable Type	3EA, Adjustable Type	
Power	220V, 1.2A 50/60Hz	220V. 3A, 50/60Hz	
Display	5.6inch all Color Touch Screen		
O ₂ Rnage	0.1 to 20.9%, ±0.1% at 5%		
O ₂ Sensor	2FO Oxygen Citicel		
Temp. Control	Digital PID Controller		
Temp. Range	Ambient +5°C to 50°C (+/- 0.1° at 37°C)		
CO ₂ Range (%)	0% to 20% (+/- 0.1 at 5%)		
CO ₂ Sensor	Carbon Dioxide (Co ₂) Sensor Module		
Sterilization	Up to 127°C (Option)		
Material (in)	Stainless Steel		
Material (Out)	Steel Plate with Powder Coating		
Heating Type	Direct Heating System (Silicone Heater)		
Door	Double Silicone Magnetic Packing Door		
Inner Door	Safety Glass Door with U-Groove Packing		
Safety Device	Over Temperature Protector Door Detector		
Utility	thermal Printer, Sample Port/Access Hole, USB Backup Port		
Humidity Range	Up to 80% at 37°C (Built-in Humidity Sensor)		
Dimension (in)	355 x 370 x 385 mm	530 x 493 x 710 mm	
Dimension (out)	440 x 490 x 570 mm	600 x 590 x 925 mm	
Weight	40 kg	80 kg	

Specification are subject to change without prior notice. Images shown are for illustrations purpose only.

WORLD WIDE MARKETING

ACZET PVT. LTD.