

KABIR INSTRUMENTS & TECHNOLOGY

CABLE FLOAT LEVEL SWITCH

Cable float switch is a control device for filling and discharging pumps, motor and magnetic valves. It is also an alarm device at certain pre-determined surface levels. It is suitable for use in non-flammable liquids at 250 volts. In dangerous environments (e.g. wells and pumping stations) we recommend 24 V voltage. In potentially explosive atmospheres (e.g. oil tanks) the Switch can be used in conjunction with (Ex) i-isolator switch units. Due to its large float casing the float



Switch has a buoyancy which guarantees smooth, trouble-free operation under all conditions. The switch has double chamber and a final remoulding finish to make it absolutely hermetic.

Installation :

Cable Float Switch is simply placed in the liquid so that the float follows the movement of the surface. The switching height differential is adjusted by moving the weight along the cable. The differential is minimum, when weight is nearest to the float. If the viscosity of the liquid is high, we recommend an extra weight on the cable.

Follower Type :

Switching element	micro switch
Life of Switch	1 Lac Operations
Rated voltage	250 VAC
Rated Current	10 Amp at 230 VAC Res
Optional	15 Amp at 230 VAC
Pressure rating	2 Bar
Heat rating	70 - 120 degrees C.
Standard Cable length	5 Mtrs (Max. 20 Mtrs)
Float material	Polypropylene (PP)
Cable insulation	PVC
Protection	IP 68
Output Contact	NO (Green) + NC (Red) + C (Black)

