



**DP PURGE ROTAMETER** 



PURGE GLASS TUBE ROTAMETER

## 2-

**"KABIR"** make Purge Glass Tube/Acrylic Rotameters are mainly used for Water, Air, Nitrogen, Purging application. These are suited with Screwed connections with orientation of Rear & Rear and several options of material for the wetted parts. Also these are optionally fitted with Constant Up - stream OR Constant Down - stream D.P.Regulator. All our products are developed as per industry norms, using premium raw material and latest technology. In addition to this, our products can be customized as per the specifications detailed by the customers.

## :-

Metering Tube	: Borosilicate Tapper Glass Tube./ Acrylic Taper Tube
Float	: S.S. / CARBOLOY
Body	: M.S. / S.S. / P.P. / Teflon.
Wetted Parts	: M.S. / S.S. / P.P. / Teflon.
End Connection	: S.S. 304/316/PVC/PP/MS
Scale	: Engraved Scale in Aluminum / S.S. 304 / 316.
Packing	: Neoprene / Teflon / Silicon.

## :-

Model	: KIT/PGTR/KIT/ABRM
Temperature	: Max 90°C
Pressure	: Max 15 Kg/Cm <sup>2</sup>
Available sizes	: 6 NB to 15 NB
Flow Ranges	: up to 0.3 - 3 LPM
End Connection	: Screwed / Hose Nipple
Orientation	: Bottom – Top / Rear – Rear
Accuracy	: ± 2% of FSD
Accessories	: 1. Constant Up - stream OR Constant Down - stream D.P.Regulator.
	2. Inbuilt Needle Valve.

Manufacturer and Exporter of Flow & Level Measuring Instruments

kabirinstru108@gmail.com • info@kabirinstruments.com

Plot No C1B-888/1/A, G.I.D.C. Estate, Makarpura, Vadodara - 390010. Gujarat INDIA.

