

112DA - 112 Litre Aluminium

Non - Refillable Cylinder

Gas Contents

112 Litres

C

Ć

Service Pressure 70 bar (1000psi)

Dimensions Height 365 mm, Diameter 90 mm

Weight

1.19 kg

Cylinder Material & Valve

Aluminium - ISO or DOT approved connection C10 Valve (5/8"-18)

Standards

NPL, UKAS or NIST standards. Manufactured gravimetrically to ISO 6142

Equipment

- Cylinder valve compatible with all major manufacturer's regulators
- Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
- On-Demand flow regulator (for non-reactive, H_2S and SO_2 mixtures)
- Variflow regulator (non-reactive gases)

Warranty

Ċ

Non-reactive gases	36 months
Ethanol	24 months
$\rm H_2S$, SO ₂ and 4 gas mixtures	12 months
NO, NH ₃ , HCN, ETO	12 months
Cl ₂ (min 5ppm)	6 months
HCI (min 5ppm)	6 months
NO ₂	6 months

Mixture Tolerances

Minor components are certified to the following analytical tolerance:

2 - 20ppm = +/- 10% 21 - 50ppm = +/- 5% 51 - 300ppm = +/- 2%

Specialty Gases and Gas Control Equipment

P.O. Box: 74582 Dubai, UAE Tel: + 971 4 3472436 Fax: +971 4 3472441 Email: info@bristol-gases.com, www.bristol-gases.com

