

GUIDELINE FOR FIXING THE TILES

- **DO NOT FIX ON FRESH SURFACE.** Complete the base plaster at latest 15 days prior to the tiles.
- Arrange the tiles from 4-5 boxes as per the pattern of your choice before fixing. see that they give desired blend of color and also ensure that you are visually satisfied with the arrangement. please note a little variation in shades do occur in all ceramic products. there will be no liability of the company after tiles are fixed.
- Do not put the tiles under any additional or out side processes like firing, printing etc. the company bears no liability in such circumstances.
- Conventional cement-sand mixture can be used to fix the porcelain's joint free tiles on the floor. However, it is recommended to use the proper adhesive only for fixing the tiles on walls. Also follow the instruction provided with such adhesive. **DO NOT USE NEAT CEMENT.**
- These tiles can be fixed free of joints. without leaving the gap between two tiles. However, it is recommended to provide a gap of 2-4mm at every six miters when the tiles are to be fixed on large areas. **DO NOT PRESS THE TILES WITH ANY HEAVY MATERIAL LIKE AN IRON HAMMER ETC.**
- Wipe with a damp sponge and polish the tiles with a soft dry cloth after FIFTEEN MINUTES of fixing.
- Use water or diluted soap solution for cleaning. Remove the residue of the soap solution by applying clean soft moist cloth moistened with clean water. **DO NOT SCRUB OR SCRATCH OR THE SURFACE.**
- The company bears no liability towards the problems (if any) raised due to adhesive or lack of good workmanship and / or supervision.

Note:

Colours & Designs shown are indicative only. Customers are requested to check the actual files for exact idea of colours & designs and to order the files after inspecting the same. Company reserves the right to change colours, designing, specifications, etc. without prior notice.

Technical Specifications

Sr. No.	PROPERTY	International Std. ISO 13006/EN 176 Group Bla	OUR VALUE
1.	 Deviation in Length	± 0.5 %	± 0.4 %
2.	 Deviation in Thickness	± 5 %	± 3 %
3.	 Straightness of Sides	± 0.5 %	± 0.5 %
4.	 Rectangularity	± 0.6 %	± 0.4 %
5.	 Surface Flatness	± 0.5 %	± 0.2 %
6.	 Water absorption*	± 3.6 %	± 3.6 %
7.	 Bending Strength	> =220kgs/cm ²	> =270kgs/cm ²
8.	 Chemical Resistance	Resistance to all alkalies (except Hydro flouric acid and its compounds)	Resistance to all alkalies (except Hydro flouric acid and its compounds)
9.	 Thermal Shock	2 Cycles	4 Cycles

Packing Details

Size	Thickness	No. of Tiles/Box	Coverage Area per Box	Weight of Box
396x396mm (39.6x39.6cm)	8.3 mm (Approx)	6 Pcs.	0.94 Sq.Mtr.	15.8 Kgs. (Approx)

Pallet Details

Box per Pallet	Pallet in Container	Sq. Mtr. per Pallet	Sq. Mtr. per Container	Boxes in Container
84 Box	21 Pallet	78.96 Sq.Mtr.	1658.16 Sq. Mtr.	1764 Box