TILE JOINT SCREED BOND - EP

(Epoxy Resin Based Tile Grout)

TECHNICAL DATA

DESCRIPTION:

TILE JOINT SCREED BOND – EP is a three component, solvent free, unique base, hardner and filler.

ADVANTAGES:

- 1. Provides hard and abrasion resistance for tile jointing.
- 2. It has an excellent chemical resistance (Acid proof).
- 3. It has an excellent waterproof.

PROPERTIES:

Pot life : 30 Minutes @ 30⁰ C Initial cure : After 24 hours @ 30⁰ C

Full Cure : $7 \text{ days } @ 30^{\circ} \text{ C}$

APPLICATIONS:

- 1. TILE JOINT SCREED BOND EP can be used for tile jointing.
- 2. It can be used for Marble jointing.

METHOD OF USAGE:

A. Surface preparation:

The joints has to be dry, sound and free from loose particle. This can be achieved by using air blower. The joints should not have a moisture content of more than 4%.

B. Mixing of TILE JOINT SCREED BOND - EP:

Mix base and hardner for about 3 mints with a stick or rod, finally add filler and mix about two minutes. Mixing has to be done to get a homogeneous colour of the mixed components.

C. Application of TILE JOINT SCREED BOND - EP:

Take out the mix and spread it on a tray or plastic sheet to increase the working time. Fill and tool the above mix firmly in the tile joints with lappum plat without any gap or voids. Use the mixed material within 30 mints. Remove excess material on the tile edges with a sponge wet with N C Thinner to get a smooth finish.

D. Coverage:

500 gms material at @ 2 mm gap width and 5 mm depth sufficient for 75 RFT.

SUPPLY: TILE JOINT SCREED BOND - EP is supplied in 500 gms pack.

SHELF LIFE:

1 year.

PRECAUTION:

TILE JOINT SCREED - EP is non – toxic. and non – flammable. Any splashes on to the eyes have to be immediately washed with plenty of water and medical advice has to be taken.

The customer should make his own trials to determine the compatibility of the product for his own purpose. All products are sold subjects to our standard terms and conditions of sale.

BOND CHEMICALS, Regd Off:3-6-268,Above ICICI Bank, Himayath Nagar,Hyderabad-500029 040-40204909, Mob. 8977044978