

CRACK SEAL BOND-U

(WATER RESISTANT ACRYLIC LATEX SEALANT)

GENERAL DESCRIPTION:

Crack seal bond-U is single component ACRYLIC polymer based sealant, which is highly water resistant and suitable for interior or exterior crack filling.

USES:

- ⌚ Crack seal bond-U easily bonds to cement , wood , painted surfaces. Easy to use , skin forms in 30 minutes.
- ⌚ Unique bridging property.
- ⌚ It can be used both interior and exterior plastered surfaces.

PROPERTIES:

FORM : PASTE
COLOUR : OFF- WHITE
BONDING CAPACITY : 2.0 N/mm²

METHOD OF USAGE:

- ⌚ Clean the joints and cracks by removing loose particles , dirt , oil and grease.
- ⌚ Widen the narrow gap in 'U' shape
- ⌚ Wash the joints and cracks with water and moisture the surface .
- ⌚ Apply with a spatula or putty knife .

STANDARDS:

Complies to IS 2645 – 1975.

PRECAUTION: Crack seal bond-U is non-toxic and non- flammable . Any splashes on to the eyes have to be immediately washed with plenty of water and medical advices has to be taken ,

SUPPLY:

Crack seal bond-U is supplied in 0.5 kg and 1 kg packs.

SHELF LIFE: 1 year

BOND CHEMICALS,
Regd Off:3-6-268,Above ICICI Bank, Himayath Nagar,Hyderabad-500029
040-40204909, Mob: 8977044978