CEMPLUG BOND – U (RAPIDSETTING CEMENTITIOUS PRODUCT)

DESCRIPTION:

CEMPLUG BOND – U is modified cement consisting of an accelerator, which set with in few minutes. It can be used in a number of situations where quick setting required.

USES:

- © **CEMPLUG BOND** U easily applied only a particular amount of water has to be added & mixed to its application.
- To rapid patching and plugging of concrete segments, sewage systems and pipes, basements.
- The unique product can be used in all places where quick setting is required.
- ① Chloride free, hence does not affect RCC.

APPLICATIONS:

- © CEMPLUG BNOD U used where quick setting is required
- ① Quick repairs of concrete, screed.
- ② Stopping leakages in tunnels, pits, and sewage systems.

METHOD OF USAGE:

Surface preparation: For repair work, the substrate has to be cleaned from loose particles, oil and grease. Areas to be patched have to be cut back into 20 mm and given good mechanical key, donot featheredge. Surfaces must be moisted with enough water prior to application of CEMPLUG BOND – U.

MIXING:

CEMPLUG BOND – U to be used after mixing with water depending upon its application. Normally mix three parts of **CEMPLUG BOND** – U with one parts of water by volume. Add required quantity water at a time, do not retemper. For larger works, it should be mixed in dry condition with 1 to 3 parts of fine sand by weight and water to get required consistency.

PRECAUTIONS:

CEMPLUG BOND - U is non – toxic and non – flammable. Any splashes on to the eyes have to be immediately washed with plenty of water and medical advice has to be taken.

SUPPLY: **CEMPLUG BOND** – **U** is supplied in 5 & 15 Kg packs.

SHELF LIFE: 1 Year.

All products are sold subject to our standard terms and conditions of sale.

BOND CHEMICALS, Regd Off:3-6-268,Above ICICI Bank, Himayath Nagar,Hyderabad-500029 040-40204909, Mob: 8977044978