

# TRUCK TYRE CHANGER


## MASKOTECH

### TR26

#### TECHNICAL DATA

Operating Pressure	: 50 - 130 Bars
Max. Wheel Dia.	: 1500 mm
Max. Wheel Width	: 760 mm
Noise Level	: <75dB
Rim Dia.	: 14" to 26"
Hyd. Pump Motor	: 1.1kw 380V/3Ph 50Hz
Gearbox Motor	: 1.8kw 380V/3Ph 50Hz
Net Weight	: 706 KG
Gross Weight	: 771 KG
Net Weight	: 2100X1650X930mm
Volume	: 3.2m cubic

 **1500MM**  
Max Wheel Diameter

 **760MM**  
Rim Width

 **1.8KW**  
POWER

 **14"-26"**  
Inside Clamp



#### FEATURES

- ▶ Lifting arm tank has centre support
- ▶ The gearbox use Tin-Bronze gear, ensures long life
- ▶ The main motor & its correlative electric parts accord with the CE Standards



#### FEATURES

The parts of hydraulic are qualified imported sub-assembly



#### FEATURES

The movable control support is easy for observing all aspects.



#### FEATURES

Electrical control cabinet adopts E-grade protective standard

\* The pictures are only for reference, the specific machines are the criterion.

# TRUCK TYRE CHANGER

## MASKOTECH

### TR57

#### TECHNICAL DATA

Operating Pressure	: 50 - 130 Bars
Max. Wheel Dia.	: 2300 mm
Max. Wheel Width	: 1100 mm
Noise Level	: <75dB
Rim Dia.	: 14" - 42"
With Extension Jaws(optional)	: 42" - 56"
Hyd. Pump Motor	: 1.1KW 380V/3Ph-50Hz
Gearbox Motor	: 2.4/3.0kW 380V/3Ph-50Hz
Net Weight	: 987 KG
Gross Weight	: 1252 KG
Packing Dimension	: 2280 X 2070 X 1070 mm
Volume	: 5 m Cubic

 **2300MM**  
Max Wheel Diameter

 **1100MM**  
Rim Width

 **1.8KW**  
Power

 **14"-56"**  
Inside Clamp



#### FEATURES

- It is used to mount / dismount the drop centre rim / tubeless wheel / wheel with ring of passenger car / truck / agricultural vehicle / industrial vehicle.
- The tool arm can automatically move horizontally & vertically.
- Tool can automatic rotate. The spindle on the mounting head, use rolling bearing design, it can be used for the tyre with huge resistance.
- Equipped with Hyd. Driven Carriage making the tyre moving on tyre changer without man power.
- The small & portable console is very convenient.
- Dual speed main shaft motor can improve the work efficiency.
- There is safe protection switch on the lifting arm.



#### FEATURES

It can reach 56" with the extension.




#### FEATURES

The small & portable console is very convenient.



#### FEATURES

The clamp exchangeable, saves service cost. The protection cover is optional.



#### FEATURES

Dual speed main shaft motor can improve the work efficiency.



#### FEATURES

Tool can automatic rotate. The spindle on the mounting head, use rolling bearing design, it can be used for the tyre with huge resistance.



#### FEATURES

The Hyd. Pump is the SPX brand is originally imported from USA securing the use life of the hyd. pump



#### FEATURES

The tool arm can automatically move horizontally & vertically

\* The pictures are only for reference, the specific machines are the criterion.